



# Glue cement C1T

# Product codes:

Reference: 910

Apparent density: 1,4 g/cm<sup>3</sup> Mixing water (+/- 1): 25,00% Granulometry: < 0,6 mm Detachment on vertical wall:  $\leq$  0,5 mm Open time after 30 m.: 20 min. Use time: 120 min. Adherence:  $\geq$  0,5 N/mm<sup>2</sup>

Placement of tiles, ceramics, stoneware, baseboards, etc. in small, medium and large sizes. Placement on interior supports. (\* see table of coatings).

### PRESENTATION

25 kg bags (approx.)

Pallets 40 bags

# **USES AND APPLICATIONS**





PRODUCTOS LAFAC, S.L. Galileo Galilei, Parc. 3 08083 CALAF (Barcelona) Tel. 93 869 84 19 e-mail: lafac@lafac.cat





Placement of tiles, ceramics, stoneware, baseboards, etc. in small, medium and large sizes. Placement on interior supports. (\* see table of coatings).

#### **APPLICATION METHOD**

Add between 25 % and 28 % of water and knead it well until obtaining a homogeneous paste. Wait a minimum of 10 minutes. Apply with a trowel.

The support must be completely set and clean. It must be resistant and have a plane with differences of less than 5 mm. Check with a 2 m ruler. of length.

Do not use at temperatures above 30 °C or below 5 °C

#### **RECOMMENDED COATINGS**

#### HANDLING

DRY PRODUCT:

Keep out of the reach of children. Avoid contact with eyes and skin.

Avoid inhalation

#### PREVENTION

In case of projection of the product dry, on eyes or skin, wash vigorously and go to a healthcare center.





PRODUCTOS LAFAC, S.L. Galileo Galilei, Parc. 3 08083 CALAF (Barcelona) Tel. 93 869 84 19 e-mail: lafac@lafac.cat





Wear appropriate gloves during application. To avoid dust and splashes it is appropriate to wear safety glasses.

# PERFORMANCE

Simple gluing: 4.5 (+/- 0.5) kg / m<sup>2</sup> (10 mm. Maximum thickness)

Double gluing: 7.5 (+/- 0.5) kg / m<sup>2</sup> (10 mm. Maximum thickness)

# STORAGE

The product should be stored under cover in a clean, dry and well-ventilated place. Non-flammable product.

Consume preferably within 12 months from the date of packaging.





PRODUCTOS LAFAC, S.L. Galileo Galilei, Parc. 3 08083 CALAF (Barcelona) Tel. 93 869 84 19 e-mail: lafac@lafac.cat

