

LAFAC

ÁRIDOS Y CEMENTOS



Porcelain glue cement C2TE

Product codes:

Reference: 900

Apparent density: 1,4 g/cm³

Mixing water (+/- 1): 25,00%

Granulometry: < 0,6 mm

Detachment on vertical wall: ≤ 0,5 mm

Open time after 30 m.: ≥ 0,5 N/mm²

Use time: 120 min

Placement of tiles, ceramics, stoneware, baseboards, etc. in small, medium and large sizes. Placement on interior supports. (* see table of coatings).

Recommended for the use of porcelain stoneware pieces with little or no absorption.

PRESENTATION

25 kg bags (approx.)

Pallets 40 bags



938 69 84 19

PRODUCTOS LAFAC, S.L.
Galileo Galilei, Parc. 3
08083 CALAF (Barcelona)
Tel. 93 869 84 19
e-mail: lafac@lafac.cat

LAFAC
ÁRIDOS Y CEMENTOS



USES AND APPLICATIONS

Placement of tiles, ceramics, stoneware, baseboards, etc. in small, medium and large sizes. Placement on interior supports. (* see table of coatings).

Recommended for the use of porcelain stoneware pieces with little or no absorption.

APPLICATION METHOD

Add between 25% and 28% of water and knead it well until obtaining a homogeneous paste. Wait a minimum of 10 minutes. Apply with a trowel. The support must be completely set and clean. It must be resistant and have a plane with differences of less than 5mm. Check with a 2m ruler. of length.

Do not use at temperatures above 30°C or below 5°C

PERFORMANCE

Simple gluing: 4.5 (+/- 0.5) kg / m² (10mm. Maximum thickness)

Double gluing: 7.5 (+/- 0.5) kg / m² (10mm. Maximum thickness)

FEATURES

ADHERENCES

Initial Adhesion: ≥ 1

Initials after heat action: ≥ 1



938 69 84 19

PRODUCTOS LAFAC, S.L.
Galileo Galilei, Parc. 3
08083 CALAF (Barcelona)
Tel. 93 869 84 19
e-mail: lafac@lafac.cat





Initials after water action: ≥ 1

Initials after freeze / thaw action: ≥ 1

RECOMMENDED COATINGS FOR THE PRODUCT

MEDIUM PIECES INTERIOR EXTERIOR MORTAR $\leq 35 \times 35$ cm - all types of absorption
Exterior CERAMICS $\leq 40 \times 40$ cm - all types of absorption Interior Exterior NATURAL
STONE $\leq 40 \times 40$ cm - all types of absorption Interior Exterior SWIMMING POOLS $\leq 40 \times 40$ cm - all types of absorption Exterior CONCRETE SLABS $\leq 40 \times 40$ cm - high and medium absorption Inside BRICKS $\leq 40 \times 40$ cm - all types of absorption

HANDLING

DRY PRODUCT:

Keep out of the reach of children.

Avoid contact with eyes and skin.

Avoid inhalation

PREVENTION

In case of projection of the product dry, on eyes or skin, wash vigorously and go to a healthcare center.

Wear appropriate gloves during application.

To avoid dust and splashes it is appropriate to wear safety glasses.



938 69 84 19

PRODUCTOS LAFAC, S.L.
Galileo Galilei, Parc. 3
08083 CALAF (Barcelona)
Tel. 93 869 84 19
e-mail: lafac@lafac.cat





STORAGE

The product should be stored under cover in a clean, dry and well-ventilated place.
Non-flammable product.

Consume preferably within 12 months from the date of packaging.



938 69 84 19

PRODUCTOS LAFAC, S.L.
Galileo Galilei, Parc. 3
08083 CALAF (Barcelona)
Tel. 93 869 84 19
e-mail: lafac@lafac.cat

