

LAFAC

ÁRIDOS Y CEMENTOS



Crushed gravel 6/12

Product codes:

Reference: 702

Arid size: ≤ 12 mm

Water soluble chlorides: $< 0,02\%$

Total sulfur content: $< 0,10\%$

Acid soluble sulfates: AS 0,8

Organic Matter Content: Sin Materia Orgánica

Fines content: F 1,5

Faces of fractures: C 50/10

Shape coefficient: SI40

Resistance to fragmentation: LA25

The 6/12 LAFAC aggregate is a product obtained in a limestone crushing process.

PRESENTATION

25 kg bags (approx.)



938 69 84 19

PRODUCTOS LAFAC, S.L.
Galileo Galilei, Parc. 3
08083 CALAF (Barcelona)
Tel. 93 869 84 19
e-mail: lafac@lafac.cat

LAFAC
ÁRIDOS Y CEMENTOS

LAFAC

ÁRIDOS Y CEMENTOS

Pallets 56 bags

Big Bags 1 Tm

APPLICATIONS

The 6/12 LAFAC aggregate is a product designed for the preparation of mass concrete, precast concrete and fillings, and road conditioning.

FEATURES

The 6/12 LAFAC aggregate is obtained through mechanical crushing, which guarantees the quality and regularity of the product.

QUALITY

The 6/12 LAFAC aggregate is subjected to tests for its different uses according to the following regulations:

UNE EN 12620 Concrete

Productos LAFAC SL guarantees that it complies with the values published in this product technical sheet.

All Mortars Manufactured by PRODUCTOS LAFAC, SL are made under the CE Conformity certificate number: 1170 / CDP / MR / .00076



938 69 84 19

PRODUCTOS LAFAC, S.L.
Galileo Galilei, Parc. 3
08083 CALAF (Barcelona)
Tel. 93 869 84 19
e-mail: lafac@lafac.cat

LAFAC
ÁRIDOS Y CEMENTOS

LAFAC

ÁRIDOS Y CEMENTOS



938 69 84 19

PRODUCTOS LAFAC, S.L.
Galileo Galilei, Parc. 3
08083 CALAF (Barcelona)
Tel. 93 869 84 19
e-mail: lafac@lafac.cat

LAFAC
ÁRIDOS Y CEMENTOS